

<b>Butterfly valve</b>		<b>Vanne papillon</b>	
<b>Specification</b>		<b>Specification</b>	
Type	wafer	Type	Oreilles de centrage
Sealing	Double direction	Etanchiete	Dans les 2 sens
Sealing test	ISO 5208	Essais d'etancheite	ISO 5208
Face to face	ISO 5752 Series 20	Ecartement	ISO 5752 Series 20
Actuator connection	ISO 5211	Embase de raccordement(actionneur)	ISO 5211
Flange drilling	PN 10/16/ASA 150	Percage de brides	PN 10/16/ASA 150
Presure	16 bar	Pression	16 bar
Temperature	Max.120°C	Temperature	Max.120°C
DN	DN40-DN200	DN	DN40-DN200
Hand lever operator	8 positions	Operateur manuel	8 positions
<b>Material</b>		<b>Matiere</b>	
Body	Cast iron	Corps	Fonte grise
butterfly	Stainless steel 304	Papillon	Inox 304
Seat	EPDM	Manchette	EPDM
Stem	Stainless steel(anti-ejection)	Axe	Inox (anit-ejectable)
Bushing	Steel(auto-lubricating)	Paliers	Acier (auto-lubricating)
<b>Weight</b>		<b>Poids</b>	
<b>DN</b>	<b>Weight (kg)</b>	<b>DN</b>	<b>poids (kg)</b>
40	3	40	3
50	3,5	50	3,5
65	4	65	4
80	5	80	5
100	7,5	100	7,5
125	14	125	14
150	16	150	16
200	23	200	23

**FLUID PROCESS**